

# **Grease Pump**

Make Your Machines Smoother, Faster



## **Ideal lubrication solutions**

ATS-ELGI, renowned leader in lubrication pumps provides a complete range of performance proven grease pumps.

Our pumps are renowned for their versatility and ease of use.



#### Benefits of ATS- ELGI make Grease pumps

- Dispensing of grease at optimum pressure
- High performance pumps that last longer
- Longer life for high quality delivery hoses
- Very convenient to use and portable

## **Application:**

- Body Greasing and Hub Greasing of Light/Heavy Commercial Vehicles
- Tightening of Traction Chain in Earth Moving Equipments
- Lubricating the Machinery in Industries
- Other greasing requirements in Automobile/Industry segments

## Hand operated grease pump



#### **Technical Specifications**

H	GH 00 004 : Grease	Ö	Output per Stroke: 3 g
	Single Cylinder, Portable & Static, Drum type with cover	0	Blocked Pressure: 140 Kg/cm <sup>2</sup>
Hose Type	Wire braided, Oil resistant, High pressure Hose	0	Delivery Hose Length: 2.2 mts
The state of the s	ID of Hose : 6 mm		Drum Capacity: 5/10/20 Kg

### Air operated grease pump



#### **Technical Specifications**

connect specifications						
∮簑	Grease Pump: GP 50 001		Air requirement (FAD) : 425 lpm			
Ů	Pressure Ratio: 50:1		Grease grade: NLGI 00,0,1,2			
Ō	Output at 8.5 Kg/cm²: 300 - 400 g	Hose Type	Wire braided, Oil resistant, High pressure Hose			
0	Max Working Pressure: 10.5 Kg/cm <sup>2</sup>	0	Delivery Hose Length: 1.1 / 2.2 mts			
0	<b>Recomm.Working Pressure:</b> 4.5 to 8.5 Kg/cm <sup>2</sup>	(Ton)	ID of Hose: 6 mm			
<u> </u>	Grease Blocked Pressure@ 8.5 Kgf/cm² Air pressure: 425 Kgf/cm²		Drum Capacity: 25/50/200 Litres			

## Oil transfer pumps models



#### **Technical Specifications**

reclinical specifications							
	Oil Transfer Pump : AN4/200 OP	(Texa)	Normal Blocked Pressure (Bar) : 29				
	Pressure Ratio: 3.5:1	0	Delivery Hose – Length (mm) : 1100				
	Free Delivery Output (lpm) : 14	Hose Type	Delivery Hose – ID (mm) : 12.7				
	Max. Working Pressure (Bar) : 10.5		Drum Capacity (Ltrs) : 200				
	Air Requirement – FAD (cfm) :11.5	<u>o</u>	Weight (Kg) : 12				
	Recommended Working Pressure (Bar): 8.5						



Visit us at: www.ats-elgi.com

Private Industrial Estate, Kurichy, Coimbatore - 641021, Tamil Nadu, India. Tel: +91-422-2589999 | Email: enquiry@ats-elgi.com

Toll-free number: 1800-425-3544

